


MULTIPLES OF SHORT-TIME PICKUP SETTING



MULTIPLES OF SHORT-TIME PICKUP SETTING



Entellisis™ Low-Voltage Switchgear with EntelliGuard™ E Low-Voltage Power Circuit Breakers

DES-105B

Available Ratings (Amperes)

Model	Frame	Current Sensor	Rating Switch Setting (Amperes)
EE08	800	400	150, 200, 225, 250, 300, 400
		800	300, 400, 450, 500, 600, 700, 800
EE16	1600	800	300, 400, 450, 500, 600, 700, 800
		1600	600, 800, 1000, 1100, 1200, 1600
EE20	2000	2000	750, 800, 1000, 1200, 1600, 2000
EE32	3200	3200	1200, 1600, 2000, 2400, 2500, 3000, 3200
EE40	4000	4000	1600, 2000, 2500, 3000, 3200, 3600, 4000
EE50	5000	5000	3200, 4000, 5000

All Voltages: 600 Vac and below

Time Overcurrent Protection Short-Time Pickup and Delay

**Note:** Maximum slope is selectable for bands 1,2,3 and 4.  
I<sup>2</sup>t slope is selectable for all bands.

Adjustments

**Short-Time Function**  
• Pickup settings: 1.5 to 9.0 in 0.5 increments and are multiples of the current setting.  
Delay bands (I<sup>2</sup>t In & Out): 1 = Min, 7 = Max

Short-Time Delay Bands (milliseconds)

Band	Commit	Clear
1	25	75
2	58	116
3	100	158
4	167	225
5	217	275
6	283	341
7	400	458