



Applications

- Power distribution
- Cable TV distribution
- Traffic signalling
- Camping sites
- Pump application

Standards

EN/IEC 61439-5

Overview of the range Page C.2

Dimensional drawings Page I.40

Specifications for tender documents Page I.62

Power dissipation values Page I.84

Column cabinets

Common features

- Pedestal and base are made of hot moulded glass fibre reinforced polyester.
- Dyed in mass RAL 7035 light grey.
- Protection degree IP44 according to EN/IEC 60259
- Total insulation 🗆
- Impact strength IK10 against external impacts according EN/IEC 62262
- Corrosion resistant.
- UV stabilised for outdoor applications.
- Suitable for use in environments from -35°C to +80°C.
 Temporary exceeding temperatures will not be harmful.
- Fixing holes for threaded inserts M6 are provided in the rear panel allowing direct mounting of busbars, mounting plate or components.
 Inserts to fix a mounting plate are installed.
- The base can be buried into the ground for stable installation of the column.
- The rainhood shape prevents water stagnation on the roof.

Features for EH4

Cabinets with hinged door - IP43

- Pedestal and base are delivered together.
- Swing handle for half profile cylindrical lock.
- Door opening angle of 180°

Features for EH4-S

Cabinets with frontal lift-off segments - ${\sf IP44}$

- Base and rear panel are moulded as one part.
- Recessed lock box for half profile cylindrical lock, protected by a vandal proof cover.
- The enclosure can be accessed by removing the frontal lift-off segments (not hinged).



FH4/FH4S - Column cahinets

EH4/EH4S - Column cabinets								
		Width	395	495	745	320	320	
		Type HxWxD		EH4-0 1600×495×224		EH4-S1 1420×320×234	EH4-S2 1850×320×234	
		Ref. No.	844130	844131	844132	844153	844185	
<u></u>	Mounting plate Hard paper with fixing bolts	Туре						
	-	HxWxD	790×370×5	790×470×5	790×720×5	600×278×5	950×278×5	
		Ref. No.	844133	844134	844135	844154	844186	



Spare keys for 843001

	844152	1		
For EH4 DIN00/	0/1- dual cylinder			
Filling pellets				
50 liter	422902	1		
			40	
5 liter	422903	1	trocker	
Pellets made ou	ıt of clay as humid			
barrier between	ground and enclo			
Recommended	filling height 20-30			
DIN 00-0: 4 bag	s with 5 liter			
Sittle at 1	1.50.19			

