



- NOTES:**
1. OPERATOR INTERFACE PANEL.
  2. MAIN INPUT CIRCUIT BREAKER.
  3. 225A SECONDARY MAIN CIRCUIT BREAKER.
  4. (42) POLE DISTRIBUTION PANELBOARDS.
  5. CT STRIP FOR BCMS (OPTIONAL).
  6. MINIMUM OF 21" CLEARANCE FOR DOOR SWING.
  7. RECOMMEND 6" CLEARANCE BETWEEN VENTILATED SIDES AND WALL FOR PROPER COOLING.
  8. BCMS CIRCUIT BOARD (OPTIONAL).

THIS DRAWING CONTAINS CONFIDENTIAL & PROPRIETARY INFORMATION AND SHALL NOT BE DISCLOSED OR COPIED WITHOUT THE EXPRESSED WRITTEN PERMISSION OF GENERAL ELECTRIC CO.

TITLE		GE ZENITH SERIES MDU, CLASSIC DESIGN	
DWG. NUMBER		50-150kvo, RH FF SIDECAR W/4 PANELBOARDS W/ BCMS OPTION	
DWG. NUMBER	REVISION		
DMG11004-GE	A2		
DRAWN BY	CHECKED BY		
RAE	KH		
DATE	DATE		
08-20-09	12-31-12		

GE Critical Power