


- NOTES:**
1. HINGED REMOVABLE PANELS PROVIDED ON SIDES.
 2. ACCESS: MINIMUM 36" FROM FRONT & REAR OF ENCLOSURE, IS REQUIRED FOR OPERATION. SIDE ACCESS IS REQUIRED FOR INSTALLATION & MAINTENANCE.
 3. APPROXIMATE WEIGHT: 550 lbs.
 4. (1) INPUT BUS, (4) MOLDED CASE CIRCUIT BREAKERS, (4) PNLBRDS W/ BCMS AND (1) MONITOR.
 5. (168) - 0.875Ø KNOCKOUTS PROVIDED.

TITLE GE ZENITH SERIES RDU, CLASSIC DESIGN
 (4) MCB; (4) PANEL W/ BCMS
 W/ MONITOR OPTION

THIS DRAWING CONTAINS
 CONFIDENTIAL & PROPRIETARY
 INFORMATION AND SHALL NOT
 BE DISCLOSED OR COPIED
 WITHOUT THE EXPRESSED,
 WRITTEN PERMISSION OF
 GENERAL ELECTRIC CO.

DWG. NUMBER	REVISION	 GE Critical Power
DWG189424-GE	A2	
DRAWN BY	CHECKED BY	
DMS	RAE	
DATE 10-11-12	DATE 12-31-12	